HEATING & COOLING

50GS 018-060
STANDARD EFFICIENCY

50GX 024-060
HIGH EFFICIENCY

SINGLE-PACKAGE
ELECTRIC COOLING UNITS
with optional ELECTRIC HEAT

- **PERFORMANCE DATA**
- **CERTIFIED DIMENSION PRINT**
- **CERTIFIED ROOF CURB DIMENSION PRINT**

© 2001 Carrier Corporation

Date:	Supersedes:	50GS018-060/50GX024-060 Single-Package Electric Cooling Units	50GS/50GX	Rev.:
JOB DATA:		LOCATION:		
BUYER:		BUYER P.O. #	CARRIER #	
UNIT NUMBER:		MODEL NUMBER:		
PERFORMANCE DATA CERTIFIED BY:			DATE:	

50GS/50GX units are self-contained, electric cooling units designed for easy installation and maintenance and dependable performance. All units have discharge openings for either horizontal or downflow configuration, and all have low sound levels. Units are intended for outdoor installation and may be located on a rooftop, or a ground-level concrete slab, or directly on the ground if local codes permit.

FEATURES

- Standard one year limited warranty for both 50GS and 50GX.
- 10 year warranty on the 50GX compressor.
- 5 year warranty on the 50GS compressor.
- Units certified and listed by UL and c-UL. Units are rated in accordance with ARI Standard 210.
- Low sound ratings.
- Units are pre-wired, pre-piped, and pre-charged for minimum installation expense.
- 12 SEER cooling efficiency, on 50GX; with Energy Star® Recognition.
- Compressor vibration isolation provides quieter operation.
- Easily converted for downflow operation with included horizontal duct covers.
- Cabinets are constructed of heavy-duty, phosphated, zinc coated pre-painted steel capable of withstanding 500 hours in salt spray.
- Easy-to-service cabinets with single-panel accessibility.
- Direct-drive multi-speed, permanent split capacitor (PSC) indoor motor is standard.
- Direct-drive, PSC outdoor fan motor.
- Coils constructed of aluminum fins bonded to copper tubes.
- Wire grille provides additional protection for the coil.
- Envirotuff™ composite rust-proof unit base pan.
- Sloped drain pan minimizes standing water in the unit.
- Refrigerant service connections make checking operating pressures easier.
- Copper & pre-coated fin coils are available from the factory by special order, for use in corrosive environments.
- Three-phase units available.

PERFORMANCE DATA

Unit Operating Weight_____lb (unit); _____lb (curb)

COOLING

Net Total Capacity _____ Btuh
Net Sensible Capacity _____ Btuh
Compressor Power Input_____kW @ _____ °F Outdoor-Air Temperature
Indoor Entering-Air db_____°F wb _____ °F
Seasonal Energy Efficiency Ratio _____
CFM _____ Ext. Static Pressure_____in. wg
Indoor Fan Motor _____Hp_____ Rpm_____Bhp

HEATING

Power Input To Unit_____ kW
Indoor Operating Temp _____°F db
Outdoor-Air Temp _____ °F (Winter Design)
Electric Capacity Required _____ Btuh
_____ KW Heater Selected

ELECTRICAL DATA

Unit Power Supply_____Volts_____Phase_____ Hz
Minimum Circuit Amps_____Maximum Overcurrent Protection_____

FIELD-INSTALLED ACCESSORIES

- ☐ Economizer
- ☐ Manual Air Damper
- ☐ Filter Rack
- ☐ Flat Roof Curb:
  - ☐ 8 in. Height
  - ☐ 14 in. Height
- ☐ Thermostat
  - ☐ Programmable
  - ☐ Non-Programmable
- ☐ Crankcase Heater
- ☐ Compressor Hard Start Kit
- ☐ 0°F Low Ambient Kit
- ☐ Square-to-Round Duct Transition Kit
- ☐ Electric Heat Package-5-20KW
- ☐ Controls Upgrade Kit
- ☐ TimeGuard® II Device

NOTES: _____

CERTIFIED DIMENSION PRINT

UNITED TECHNOLOGIES CARRIER
P O BOX 4808
SYRACUSE N. Y.
13221

THIS DOCUMENT IS THE PROPERTY OF CARRIER CORPORATION AND IS DELIVERED UPON THE EXPRESS CONDITION THAT THE CONTENTS WILL NOT BE DISCLOSED OR USED WITHOUT CARRIER CORPORATION'S WRITTEN CONSENT.

SUBMISSION OF THESE DRAWINGS OR DOCUMENTS DOES NOT CONSTITUTE PART PERFORMANCE OR ACCEPTANCE OF CONTRACT

DIMENSIONS IN [] ARE IN INCHES

UNIT	ELECTRICAL CHARACTERISTICS	UNIT WT. LBS.	UNIT WT. KG.	UNIT HEIGHT "A"	CENTER OF GRAVITY MM/IN X	Y	Z
50GS018	208-230-1-60	254	115.2	889.5[35.02]	508.0[20.0]	330.2[13.0]	381.0 [15.0]
50GS024	208-230-1-60	260	117.9	889.5[35.02]	482.6[19.0]	330.2[13.0]	381.0 [15.0]
50GS030	208/230-1-60, 208/230-3-60	258	117.0	889.5[35.02]	482.6[19.0]	355.6[14.0]	381.0 [15.0]
50GS036	208/230-1-60, 208/230-3-60, 460-3-60	262	118.8	889.5[35.02]	508.0[20.0]	355.6[14.0]	330.2 [13.0]
50GS042	208/230-1-60, 208/230-3-60, 460-3-60	294	133.3	889.5[35.02]	482.6[19.0]	355.6[14.0]	330.2 [13.0]
50GX024	208-230-1-60	270	122.5	889.5[35.02]	469.9[18.5]	368.3[14.5]	406.4 [16.0]
50GX030	208/230-1-60, 208/230-3-60	291	132.0	991.1[39.02]	495.3[19.5]	393.7[15.5]	447.0 [17.6]
50GX036	208/230-1-60, 208/230-3-60, 460-3-60	299	135.6	889.5[35.02]	495.3[19.5]	387.4[15.3]	419.1 [16.5]



TOP VIEW

REQUIRED CLEARANCES TO COMBUSTIBLE MATL.

	MILLIMETERS [IN]
TOP OF UNIT	355.6 [14.00]
DUCT SIDE OF UNIT	50.8 [2.00]
SIDE OPPOSITE DUCTS	355.6 [14.00]
BOTTOM OF UNIT	12.7 [0.50]
ELECTRIC HEAT PANEL	914.4 [36.00]

NEC. REQUIRED CLEARANCES.

	MILLIMETERS [IN]
BETWEEN UNITS, POWER ENTRY SIDE	1066.8 [42.00]
UNIT AND UNGROUNDED SURFACES, POWER ENTRY SIDE	914.0 [36.00]
UNIT AND BLOCK OR CONCRETE WALLS AND OTHER GROUNDED SURFACES, POWER ENTRY SIDE	1066.8 [42.00]

REQUIRED CLEARANCE FOR OPERATION AND SERVICING

	MILLIMETERS [IN]
EVAP. COIL ACCESS SIDE	914.0 [36.00]
POWER ENTRY SIDE	914.0 [36.00]
(EXCEPT FOR NEC REQUIREMENTS)	
UNIT TOP	914.0 [36.00]
SIDE OPPOSITE DUCTS	914.0 [36.00]
DUCT PANEL	304.8 [12.00]*

*MINIMUM DISTANCES: IF UNIT IS PLACED LESS THAN 304.8 [12.00] FROM WALL SYSTEM, THEN SYSTEM PERFORMANCE MAYBE COMPROMISED.



LEFT SIDE VIEW

FRONT VIEW



RIGHT SIDE VIEW



REAR VIEW

DATE 09/03/99
SUPERSEDES XX
50GS018-042/50GX024-036 PACKAGED AIR CONDITIONER
50GS500063
REV -

C01010

Cut along dotted line

Cut along dotted line

CERTIFIED DIMENSION PRINT

UNITED TECHNOLOGIES CARRIER — P O BOX 4808 SYRACUSE N. Y. 13221

THIS DOCUMENT IS THE PROPERTY OF CARRIER CORPORATION AND IS DELIVERED UPON THE EXPRESS CONDITION THAT THE CONTENTS WILL NOT BE DISCLOSED OR USED WITHOUT CARRIER CORPORATION'S WRITTEN CONSENT.

SUBMISSION OF THESE DRAWINGS OR DOCUMENTS DOES NOT CONSTITUTE PART PERFORMANCE OR ACCEPTANCE OF CONTRACT

UNIT	ELECTRICAL CHARACTERISTICS	UNIT WT. LBS.	UNIT WT. KG.	UNIT HEIGHT "A"	CENTER OF GRAVITY MM/IN X	Y	Z
50GS048	208-230-1-60, 208/230-3-60, 460-3-60	324	147.0	990.2[38.98]	508[20.0]	431.8[17.0]	431.8 [17.0]
50GS060	208-230-1-60, 208/230-3-60, 460-3-60	389	176.4	990.2[38.98]	482.6[19.0]	406.4[16.0]	431.8 [17.0]
50GX042	208-230-1-60, 208/230-3-60, 460-3-60	321	145.6	990.2[38.98]	520.7[20.5]	425.5[16.8]	421.6 [16.6]
50GX048	208-230-1-60, 208/230-3-60, 460-3-60	326	147.8	990.2[38.98]	495.3[19.5]	447.6[17.6]	457.2 [18.0]
50GX060	208-230-1-60, 208/230-3-60, 460-3-60	399	181.0	1091.1[42.98]	520.7[20.5]	412.8[16.3]	447.0 [17.6]

DIMENSIONS IN [] ARE IN INCHES



TOP VIEW

REQUIRED CLEARANCES TO COMBUSTIBLE MATL.

	MILLIMETERS [IN]
TOP OF UNIT	355.6 [14.00]
DUCT SIDE OF UNIT	50.8 [2.00]
SIDE OPPOSITE DUCTS	355.6 [14.00]
BOTTOM OF UNIT	12.7 [0.50]
ELECTRIC HEAT PANEL	914.4 [36.00]

NEC. REQUIRED CLEARANCES.

	MILLIMETERS [IN]
BETWEEN UNITS, POWER ENTRY SIDE	1066.8 [42.00]
UNIT AND UNGROUNDED SURFACES, POWER ENTRY SIDE	914.0 [36.00]
UNIT AND BLOCK OR CONCRETE WALLS AND OTHER GROUNDED SURFACES, POWER ENTRY SIDE	1066.8 [42.00]

REQUIRED CLEARANCE FOR OPERATION AND SERVICING

	MILLIMETERS [IN]
EVAP. COIL ACCESS SIDE	914.0 [36.00]
POWER ENTRY SIDE	914.0 [36.00]
(EXCEPT FOR NEC REQUIREMENTS)	
UNIT TOP	914.0 [36.00]
SIDE OPPOSITE DUCTS	914.0 [36.00]
DUCT PANEL	304.8 [12.00]*

*MINIMUM DISTANCES: IF UNIT IS PLACED LESS THAN 304.8 [12.00] FROM WALL SYSTEM, THEN SYSTEM PERFORMANCE MAYBE COMPROMISED.



LEFT SIDE VIEW

FRONT VIEW



RIGHT SIDE VIEW



REAR VIEW

DATE 09/08/99 — SUPERSEDES - - — 50GS048-060/50GX042-060 PACKAGED AIR CONDITIONER — 50GS500064 — REV *

CERTIFIED DIMENSION PRINT

SUBMITTAL

Roof Curb for Small Cabinet

SUBMITTED TO _____
COMPANY: _____
DRAWN BY: A.L.L.
JOB NAME: _____
EQUIPMENT: _____
NOTES: _____

ODS Catalog Ordering No.	A
CPCRFCURB006A00	8"
CPCRFCURB007A00	14"

Feature:
- Constructed of heavy gage galvanized steel.
- Roofcurb ships knocked down in corrugated box.
- Quick-clip design for easy field assembly.
- Insulated deck pan.
- Gasketing package and hardware included.
- Wood nailer provided.







* Duct size

SIDE VIEW

C00077

Cut along dotted line

Cut along dotted line

CERTIFIED DIMENSION PRINT

SUBMITTAL

Roof Curb for Large Cabinet

SUBMITTED TO: _____
COMPANY: _____
DRAWN BY: M. HARGIS
JOB NAME: _____
EQUIPMENT: _____
NOTES: _____

FEATURES:

- Constructed of heavy gage galyanized steel.
- Quick-clip design for easy field assembly.
- Ships knocked down w/corrugated box.
- Gasket package for complete outer perimeter flange and around duct openings.
- Wood nailer provided.



Side View



ODS Catalog Ordering No.	A
CPRFCURB008A00	8"
CPRFCURB009A00	14"

C00078

Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice and without incurring obligations.